

> **High Speed 1-D/2-D Handheld Barcode Reader**

DataMan 8050 barcode readers bring Cognex's patented algorithms to a new, lightweight industrial handheld platform. DataMan 8050 reads 1-D and 2-D barcodes with incredible speed every time even if it's damaged, smudged, scuffed or poorly marked. And, at an economical price point.

> **Modular Design Easily Adapts to Meet Your Needs**

With field interchangeable communication modules, one reader can be configured to meet specific communication needs. Available with both corded and wireless modules.

> **Rugged Industrial Design**

The DataMan 8050 barcode reader is constructed to handle the harshest environments. Other industrial features include: lanyard hook for easy retractor mounting, bright centralized aimer for clear targeting, loud beeper and indicator lights provide operator feedback.



DataMan 8050 readers are equipped with Cognex's world class barcode reading algorithms and designed to withstand harsh factory floor conditions. The best-in-class algorithms decode even the most challenging barcodes quickly and easily. And, the flexible modular design ensures the DataMan 8050 readers are ready to meet ever changing communication needs.

Proven Performance

The DataMan 8050 readers are ideal for applications in any manufacturing environment that require robust barcode technology and reliable reading performance:



- Automotive body and assembly
- Electronics manufacturing
- Incoming inspection
- Shipping
- Automotive kitting
- Aerospace
- Packaging
- Receiving

High Speed 1-D/2-D Reading Performance

- Cognex's patented algorithms, 1DMax+ with HOTBARS™, enables the DataMan 8050 barcode reader to decode the most challenging 1-D barcodes quickly and easily, at more angles and in any orientation.
- Class-leading 2-D algorithms read many 2-D symbologies even when damaged, obstructed or with perspective distortion. Supported 2-D symbologies include: DataMatrix, QR, PDF417, MaxiCode and Aztec.
- Best-in-class reading performance means 8050 reads: damaged, plastic wrapped, direct inkjet, low contrast, poorly printed, scraped, obstructed, uneven, torn, small and smudged barcodes.

Cognex® DataMan 8000 readers set the new performance standard when it comes to industrial barcode reading. These industry-leading readers introduced several firsts to industrial handheld scanner capabilities. To learn more about the DataMan 8050X, 8100 and 8500 handheld ID readers, visit www.cognex.com/dataman.

Flexible and Easy Integration

- Intuitive Quick Setup Sheets: allow the user to configure the communication and data formatting settings for many common applications.
- Custom Setup Sheets can be printed out from within Setup Tool.
- DataMan Setup Tool Software: view images, complete suite of tools, Java Scripting, PERL Scripting and a variety of advanced data formatting options.



Specifications

<u>Dimensions</u>	210 mm x 115 mm x 85 mm
<u>Weight</u>	Corded: 0.615 lbs./279 g Wireless: 0.728 lbs./330 g
<u>Operating Temperature</u>	0°C to 40°C (32°F to 104°F)
<u>Storage Temperature</u>	-40°C to 60°C (-40°F to 140°F)
<u>Maximum Humidity</u>	95% (non-condensing)
<u>Material</u>	Polycarbonate housing with overmold
<u>Imager</u>	752 x 480 Global Shutter Sensor
<u>Aiming</u>	Centralized green LED aimer
<u>Status Outputs</u>	LED and Beeper
<u>Communications</u>	Serial Module: RS-232, USB-CDC and USB-HID Keyboard Output Bluetooth Intelligent Base Station: RS-232, USB-CDC and USB-HID Keyboard Output
<u>Symbologies</u>	1-D: UPC/EAN/JAN; Codabar, Interleaved 2 of 5, Code 39, Code 128, and Code 93, GS1 Databar, PDF417, Micro PDF417 2-D: Data Matrix, QR, MicroQR, Aztec, MaxiCode
<u>Lighting</u>	Integrated LED with near/far optics
<u>Power Supply Requirements</u>	5V-6V DC, 2.5W LPS or NEC Class 2 power supply Intelligent Base Station: 24V DC
<u>Environmental</u>	Compliant with RoHS directive 2002/98/EEC
<u>Regulatory</u>	Electrical EMI/RFI
	CE, CSA, UL, 60950 FCC Part 15, CE (EMC and R&TTE Directives), ICES-003, RSS-210 Issue 8, KCC
<u>Data Validation</u>	US DoD UID Guidelines, GS-1, ISO15434 and ISO15418
<u>Operating System</u>	Microsoft® Windows® XP, Windows 7 and Windows 8

Scan Chart

<u>Type</u>	Depth of Field
<u>7 mil 2-D Code</u>	Up to 40 mm
<u>10 mil 2-D Code</u>	Up to 80 mm
<u>Code39 6 mil</u>	Up to 90 mm

Contact:

ORITRONIC SDN BHD

No 11A Jalan TPP 1/13. Taman Industri Puchong, 47100 Puchong Selangor

T: (603) 8062 2681 / 4681

F: (603) 8060 3681

E: enquiry@oritronic.com.my

W: www.oritronic.com.my