

RX2-B (Basic Model)

This model is designed for basic coding applications in everyday environments. Printing with highest quality and reliability for many industries such as food, beverage, chemical and personal care.



FEATURES

- Accurate and precise printing
- Brighter and clearer touch screen
- Improved ink circulation block
- User friendly operation
- USB memory-compatible

STANDARD SPECIFICATION

Item		Model
		RX2-BD 160W
Nozzle size		65mm
Max. print line number		Up to 3 lines
Max. Number of print characters		Up to 60 characters
Front (Horizontal x Vertical)	5x5	√
	5x7(8), 9x7(8)	√
	7x10	√
	11x11	√ (Chinese only)
	10x12	√
	12x16	√
	18x24	√
Character height		2 - 10 mm
Display & input device		WYSIWYGdesign Display: TFT LCD (10.4" color), Backlight provided Input device: Touch panel, input sound provided
Screen language (2 language selectable)		English, Chinese, Korea, Thai, Vietnamese, German, French, Dutch, Italian, Spanish, Portuguese, Swedish, Danish, Greek, Russian, Czech, Polish, Arabic, Serbian, Turkish, Hungarian, Blugarian, Catalan, Romanian, Finnish, Norwegian available
Max. print rate (character per second) (Font5x5,space1,1line)		Up to 765
Standard characters		Alphanumeric (A-Z, a-z, 0-9), Symbols (27), Space: total 90
User pattern		Each dot matrix 50 patterns
Print functions		Calendar, Count, Font mixture , Passwords security, etc.
Message storage capacity		24 messages
Input signal		Print target detection, Rotary encoder pulse (NPN/PNP selectable)
Output signal		Print ready, Fault, Warning (NPN only)
Data interface		OPTION (RS-232C at baud rates selectable up to 115,200bps)
External memory		USB for user data storage
Head cable length / angle		4m (inline/90 degrees)
Operating temperature range		0-45°C (JP-K67, JP-K69 Ink)
Humidity range		30-90% R.H. (no condensation)
Power supply (Auto voltage selection)		AC100-120/220-240C±10% 50/60 Hz 150VA (AC Inlet)
Approval		CE, UL, cUL, C-Tick, FOC, ICES
Overall size (W x D x H)		400x320x480mm
Environmental protection		IP55
Approximate weight		25kg

Contact:
ORITRONIC SDN BHD
No 11 A Jalan TPP 1/13, Taman Industri Puchong, 47100 Puchong Selangor
T: (603) 8062 2681 / 4681 F: (603) 8060 3681 E: enquiry@oritronic.com.my W: www.oritronic.com.my